AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Claim 1 (Currently amended): A mounting process simulation program recorded on a computer-readable medium that executes a simulation of a mounting process composed of a plurality of steps, the program causing the computer to execute:

a first simulation executing step of executing a simulation based on a first condition selected for a first step;

a simulation condition deciding step of selecting a simulated result from the first simulation executing step as a simulation condition for a second step positioned subsequent to the first step; and

a second simulation executing step of executing a simulation of the second step based on a second condition comprising the simulation condition and at least a third condition that yields a second simulation result that is stored on the computer readable medium.

Claim 2 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, wherein analysis result data are generated at every step based on a plurality of conditions which were previously simulated, and

the second simulation executing step executes the simulation of the second step by sampling the analysis result data simulated based on the second condition.

Claim 3 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, wherein analysis result data are generated at every step based on a plurality of conditions which were previously simulated, and

the second simulation executing step executes the simulation of the second step by executing an interpolation calculation using the analysis result data simulated based on a preceding or succeeding condition of the second condition.

Claim 4 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 2 or 3, wherein the analysis result data are generated at every step based on a plurality of conditions which were previously simulated, and

the second simulation executing step executes the simulation of the second step by converting the analysis result data generated by other device into a predetermined data format.

Claim 5 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 4, wherein at least one of the following types of data are generated by an external system and is selected as the analysis result data: data simulated previously at every step via a CAE tool,

mounting resultant data from a mounting equipment provided to a mounting site at every step, the mounting resultant data comprising fraction defective data and production results; and experimental data derived by an experiment in which an operation in each step is supposed;

wherein the type of data selected as the analysis result data is converted to a common format.

Claim 6 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, further comprising an animation displaying step of displaying three-dimensionally an animation to indicate a result simulated in the second simulation executing step on a display device, by reading previously-stored animation elements based on a definition file in which an operation sequence is defined at every step.

Claim 7 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, wherein the second simulation executing step includes a condition acquiring step of reading a condition selected in response to an input from a condition database in which a plurality of conditions are stored previously in combination, and adding the condition to the second condition.

Claim 8 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 7, wherein the

condition acquiring step further reads data from a CAD system in response to the input and adds the data to the second condition.

Claim 9 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, wherein the first simulation executing step executes the simulation to contain production variation in the first step,

the simulation condition deciding step decides the result simulated in the first simulation executing step to contain the production variation as the simulation condition, and

the second simulation executing step executes the simulation of the second step based on the second condition which contains the production variation.

Claim 10 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, wherein the first simulation executing step executes the simulation based on a change of a control item set in the first step as the first condition,

the simulation condition deciding step decides the result simulated based on the change of the control item in the first simulation executing step as the simulation control, and

the second simulation executing step executes the simulation of the second step based on the second condition which contains the result simulated based on at least the change of the control item.

Claim 11 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, further causing the computer to execute

a reliability evaluating step of executing a reliability evaluation of a product manufactured in the mounting process by using the result simulated in the second simulation executing step.

Claim 12 (Previously presented): A mounting process simulation program recorded on a computer-readable medium according to claim 1, further causing the computer to execute

a fraction defective calculating step of calculating a fraction defective of a product manufactured in the first step and the second step, by using results simulated in the first simulation executing step and the second simulation executing step.

Claim 13 (Previously presented): A mounting process simulation system provided to steps of a mounting process composed of a plurality of steps to execute a simulation of the mounting process, comprising:

an inputting portion for inputting a plurality of conditions to execute the simulation;

an executing portion for executing the simulation based on condition input from the inputting portion; and

an outputting portion for outputting a result of the simulation executed by the executing portion;

wherein the executing portion includes:

a condition table forming portion that forms a condition table that lists a simulation condition of a second step positioned subsequently to a first step, whereby the condition table is formed by using a simulation result simulated based on a first condition selected for at least a first step, and

a simulation result outputting portion that executes the simulation of the second step based on condition data from the condition table and a condition input from the inputting portion and outputs a result to the outputting portion.

Claim 14 (Currently amended): A mounting process simulation method of executing a simulation of a mounting process composed of a plurality of steps comprising:

a first simulation executing step of executing a simulation based on a first condition selected for a first step;

a simulation condition deciding step of selecting a simulated result from the first simulation executing step as a simulation condition for a second step positioned subsequent to the first step; and

a second simulation executing step of executing a simulation of the second step based on a second condition containing at least the simulation condition and at least a third condition to yield a second simulated result that is stored on the computer readable medium.

Claim 15 (Previously presented): The mounting process simulation program recorded on a computer-readable medium according to claim 1, wherein the first, second and third conditions are selected from a plurality of conditions.

Claim 16 (Previously presented): The mounting process simulation program recorded on a computer-readable medium according to claim 15, wherein the plurality of conditions comprises solder conditions, printing mask conditions, printing device conditions, substrate conditions, mounting device conditions, solder printing conditions, parts conditions, and reflow furnace conditions.

Claim 17 (Previously presented): The mounting process simulation method according to claim 14, wherein the first, second and third conditions are selected from a plurality of conditions.

Claim 18 (Previously presented): The mounting process simulation method according to claim 17, wherein the plurality of conditions comprises solder conditions, printing mask conditions, printing device conditions, substrate conditions, mounting device conditions, solder printing conditions, parts conditions, and reflow furnace conditions.

Claim 19 (Previously presented): The mounting process simulation method according to claim 17 further comprises displaying the second simulated result as a

Appln. No. 10/767,658 Amendment dated November 13, 2007 In Response to Office Action dated August 10, 2007

three-dimensional animation by reading previously-stored animation elements based on a definition file in which an operation sequence is defined at every step.